



**Vulcano**  
Mica




**Vulcano**  
Vapor



**Vulcano**  
Pompeii



**Vulcano**  
Strata



**Vulcano**  
Umber



**Vulcano**  
Crater



**Vulcano**  
Moraine



**Vulcano**  
Lava



**Vulcano**  
Fossil



**Vulcano**  
Cinder



**Vulcano**  
Ash



**Sierra**  
Muscat



**Sierra**  
White



**Sierra**  
Vanilla



**Sierra**  
Taupe



**Sierra**  
Mushroom



**Sierra**  
Mahogany



**Sierra**  
Straw



**Sierra**  
Saddle



**Sierra**  
Crimson



**Sierra**  
Vino



**Sierra**  
Cafe



**Sierra**  
Ash



**Sierra**  
Black



**Sierra**  
Baltic



**Lena**  
Acqua



**Lena**  
White



**Lena**  
Dover



**Lena**  
Ming



**Lena**  
Putty



**Lena**  
Camel




**Lena**  
Butterscotch




**Lena**  
Caramel



**Lena**  
Clay



**Lena**  
Cardinal



**Lena**  
Chateau



**Lena**  
Greystone



**Lena**  
Safari



**Lena**  
Café Latte



**Lena**  
Linen



**Lena**  
Alba



**Lena**  
Nutmeg




**Lena**  
Sequoia



**Lena**  
Onda



**Lena**  
Evergreen




**Lena**  
Tahoe



**Lena**  
Azure




**Lena**  
Cobalt




**Lena**  
Pewter



**Lena**  
Espresso



**Lena**  
Sterling



**Lena**  
Black

# LEATHER CARD

PATTERN	RAW MATERIAL	FINISH	THICKNESS	HIDE SIZE	ABRASION RESISTANCE	DRY RUBBING	WET RUBBING	FLAME RESISTANCE	GRADES
Lena	European and New Zealand	Semi-Aniline	0.9 to 1.0 mm	Avg 48 sq ft	ASTM D 3884-92 500 gram load: 1000 cycles	500 Rubs: IUF 450 UNI EN ISO 11640; > 4 grey scale	150 Rubs: IUF 450 UNI EN ISO 11640; > 4 grey scale	UFAC 1, CAL TB 117-2013, NFPA 260	L1
Sierra	Australian	Semi-Aniline	1.0 to 1.2 mm	Avg 50-60 sq ft	ASTM D 3884-92 500 gram load: 2500 cycles (CS-10 wheels)	500 Rubs: IUF 450 UNI EN ISO 11640; > 4-5 grey scale	150 Rubs: IUF 450 UNI EN ISO 11640; > 4 grey scale	UFAC 1, CAL TB 117-2013, NFPA 260	L1
Vulcano	European and New Zealand	Semi-Aniline	0.9 to 1.0 mm	Avg 48 sq ft	ASTM D 3884-92 500 gram load: 1000 cycles	500 Rubs: IUF 450 UNI EN ISO 11640; > 4 grey scale	150 Rubs: IUF 450 UNI EN ISO 11640; > 4 grey scale	UFAC 1, CAL TB 117-2013, NFPA 260	L1

Note: Grades based on March 1, 2016 price list.

<b>Processing and Finishing</b>	Green Hide Leathers are processed using low emission mineral tanning formulas which are environmentally friendly. The hides are retanned in aged oak drums using vegetable agents, natural fat liquors and oils along with dyes that ensure the leather is properly through dyed. Complies with the strict regulations of the EU environmental normative CE2000/53. Water-based finishes are applied to provide an even coloration and protection to the leather.
<b>Lena Leather</b>	Full grain leather with even coloration throughout the entire hide. Superior selection of European and New Zealand cattle hides are hand selected for Lena. These hides are recognized industry wide for their clean surfaces and excellent cutting yields. Luxurious soft hand and smooth supple surface make this one of the most beautiful leathers available. The protective finish allows Lena to be suitable for most public and private environments.
<b>Sierra Leather</b>	Top grain leather with even coloration throughout the entire hide. Superior selection of Australian cattle hides are hand selected for Sierra. A gentle buffing and grain enhancement is applied to provide Sierra with a consistent grain structure throughout each hide and from hide to hide. Sierra is recognized industry wide for its clean surfaces and excellent cutting yields. Soft hand combined with superior technical specifications make this leather suitable for most high traffic interior applications from furniture, automotive and marine.
<b>Vulcano Leather</b>	Vulcano combines distressed leather aesthetics with the durability of modern tanning. Hand selected European and New Zealand hides are aniline dyed with a classic marbled crackle effect. A protective non-scratch finish allows use in high traffic areas and, makes Vulcano suitable for public and private environments.

Made in Italy



Please make an appointment to visit us at:  
 3401 Madison Street  
 Skokie, IL 60076  
[www.appliedergonomics.com](http://www.appliedergonomics.com)

Call us: (847) 679-5148  
 Toll-free: (844) 859-9247  
 Fax: (847) 933-0018

Email the President directly  
[jmeltzer@appliedergonomics.com](mailto:jmeltzer@appliedergonomics.com)



Tel: 336.315.9720 | [greenhides.com](http://greenhides.com) | 888.326.0122